


**South Coast AQMD**  
**Site Survey Report for Anaheim-Loara School**  
*Last updated: May, 2015*



AQS ID	ARB Number	Site Start Date	Reporting Agency and Agency Code
06059007	30178	08/2001	South Coast AQMD (061)

Site Address	County	Air Basin	Latitude	Longitude	Elevation
1630 Pampas Ln Anaheim, CA 92802	Orange	South Coast	33° 49' 50"N	117° 56' 18"W	39



## Detailed Site Information

Local site name	Anaheim-Loara School			
AQS ID	060590007			
GPS coordinates (decimal degrees)	Latitude: 33° 49' 50" Longitude: 117° 56' 18"			
Street Address	1630 Pampas Ln, Anaheim, CA 92802			
County	Orange			
Distance to roadways (meters)	7.5 – 10.5; 420 meters			
Traffic count (AADT, year)	< 500 / 2012; I-5/Euclid, 256,000, I-5, 2011			
Groundcover (e.g. asphalt, dirt, sand)	Grass			
Representative statistical area name (i.e. MSA, CBSA, other)	31080-Los Angeles-Long Beach-Anaheim, MSA			
Pollutant, POC	Carbon Monoxide, 1	Nitrogen Dioxide, 5	Ozone, 1	PM10, 1
Parameter code	42101	42602	44201	See Table 26
Basic monitoring objective(s)	NAAQS	NAAQS	NAAQS	NAAQS
Site type(s)	Population Exposure	Population Exposure	Population Exposure	Population Exposure
Monitor (type)	SLAMS	SLAMS	SLAMS	SLAMS
Instrument manufacturer and model	Horiba APMA 370	Thermo 42i	Thermo 49i	GMW 1200 SSI
Method code	158	074	047	063, 102
FRM/FEM/ARM/ other	FRM	FRM	FEM	FRM
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Analytical Lab (i.e. weigh lab, toxics lab, other)	N/A	N/A	N/A	SCAQMD
Reporting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Urban	Neighborhood	Neighborhood
Monitoring start date (MM/DD/YYYY)	08/2001	08/2001	08/2001	08/2001
Current sampling frequency (e.g. 1:3, continuous)	1:1	1:1	1:1	1:6
Calculated sampling frequency (e.g. 1:3/1:1)	N/A	N/A	N/A	1:6
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	01/01-12/31
Probe height (meters)	4.5	4.5	4.5	2.5
Distance from supporting structure (meters)	1.9	1.9	1.9	1
Distance from obstructions on roof (meters)	N/A	N/A	N/A	N/A
Distance from obstructions not on roof (meters)	N/A	N/A	N/A	N/A

Distance from trees (meters)	6 (palm tree)	6 (palm tree)	6 (palm tree)	6 (palm tree)
Distance to furnace or incinerator flue (meters)	N/A	N/A	N/A	N/A
Distance between collocated monitors (meters)	N/A	N/A	N/A	2.8
Unrestricted airflow (degrees)	360°	360°	360°	360°
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	Teflon	Teflon	Teflon	N/A
Residence time for reactive gases (seconds)	5.6	6.8	6.7	N/A
Will there be changes within the next 18 months? (Y/N)	No	No	No	No
Is it suitable for comparison against the annual PM2.5? (Y/N)	N/A	N/A	N/A	N/A
Frequency of flow rate verification for manual PM samplers	N/A	N/A	N/A	Monthly
Frequency of flow rate verification for automated PM analyzers	N/A	N/A	N/A	N/A
Frequency of one-point QC check for gaseous instruments	Nightly	Nightly	Nightly	N/A
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	05/9/2014	05/9/2014	05/9/2014	N/A
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	N/A	N/A	N/A	5/27/14, 11/18/2014

Pollutant, POC	Continuous PM10, 3	Continuous PM2.5, 3	Speciated PM2.5, 11	24 Hour PM2.5, 1
Parameter code	81102	88101	See Table 26	See Table 26
Basic monitoring objective(s)	NAAQS	NAAQS	NAAQS	NAAQS
Site type(s)	Population Exposure	Population Exposure	Population Exposure	Population Exposure
Monitor (type)	SLAMS	SLAMS	SLAMS	SLAMS

Instrument manufacturer and model	Met One BAM 1020	Met One BAM 1020	Met One SASS	Andersen RAAS PM2.5
Method code	122	170	See Table 26	780, 120
FRM/FEM/ARM/ other	FEM	FEM	Other	FRM
Collecting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Analytical Lab (i.e. weigh lab, toxics lab, other)	N/A	N/A	SCAQMD	SCAQMD
Reporting Agency	SCAQMD	SCAQMD	SCAQMD	SCAQMD
Spatial scale (e.g. micro, neighborhood)	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Monitoring start date (MM/DD/YYYY)	03/04/2010	08/2001	08/2001	08/2001
Current sampling frequency (e.g. 1:3, continuous)	1:1	1:1	1:6	1:1
Calculated sampling frequency (e.g. 1:3/1:1)	N/A	N/A	No CFR mandated sampling schedule.	1:3
Sampling season (MM/DD-MM/DD)	01/01-12/31	01/01-12/31	01/01-12/31	01/01-12/31
Probe height (meters)	4.8	4.8	2.9	2.9
Distance from supporting structure (meters)	2.2	2.2	2.2	1
Distance from obstructions on roof (meters)	N/A	N/A	N/A	N/A
Distance from obstructions not on roof (meters)	N/A	N/A	N/A	N/A
Distance from trees (meters)	6 (palm tree)	6 (palm tree)	6 (palm tree)	6 (palm tree)
Distance to furnace or incinerator flue (meters)	N/A	N/A	N/A	N/A
Distance between collocated monitors (meters)	2.8	3.9	N/A	3.9
Unrestricted airflow (degrees)	360°	360°	360°	360°
Probe material for reactive gases (e.g. Pyrex, stainless steel, Teflon)	N/A	N/A	N/A	N/A
Residence time for reactive gases (seconds)	N/A	N/A	N/A	N/A
Will there be changes within the next 18 months? (Y/N)	No	No	No	No



Is it suitable for comparison against the annual PM2.5? (Y/N)	N/A	No, unless manual sampler has missing data.	N/A	Yes
Frequency of flow rate verification for manual PM samplers	N/A	N/A	Monthly	Monthly
Frequency of flow rate verification for automated PM analyzers	Monthly	Monthly	N/A	N/A
Frequency of one-point QC check for gaseous instruments	N/A	N/A	N/A	N/A
Last Annual Performance Evaluation for gaseous parameters (MM/DD/YYYY)	N/A	N/A	N/A	N/A
Last two semi-annual flow rate audits for PM monitors (MM/DD/YYYY, MM/DD/YYYY)	06/20/2014, 12/07/2014	06/20/2014, 12/07/2014	11/22/2013, 06/28/2013	11/18/2014, 05/27/2014

**Anaheim-Loara School  
Site Photos**



**Looking North from the probe.**



**Looking East from the probe.**



**Looking South from the probe.**



**Looking West from the probe.**

**Anaheim-Loara School  
Site Photos (Cont.)**



**Looking at the probe from the North.**



**Looking at the probe from the East.**



**Looking at the probe from the South.**



**Looking at the probe from the West.**